

Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) Publication number : 0 509 843 A3

(12)

## EUROPEAN PATENT APPLICATION

(21) Application number : 92303498.7

(22) Date of filing : 16.04.92

(51) Int. Cl.<sup>5</sup> : G01S 13/42, G01S 13/22,  
G01S 13/58, G01S 13/87,  
H01Q 3/46

(30) Priority : 16.04.91 US 685791

(43) Date of publication of application :  
21.10.92 Bulletin 92/43

(84) Designated Contracting States :  
DE FR GB IT

(88) Date of deferred publication of search report :  
12.05.93 Bulletin 93/19

(71) Applicant : GENERAL ELECTRIC COMPANY  
1 River Road  
Schenectady, NY 12345 (US)

(72) Inventor : Freedman, Jerome Edwin  
742 Mill Street  
Moorestown, New Jersey 08057 (US)  
Inventor : Perry, Michael Stockum  
300 Millside Lane  
Haddonfield, New Jersey 08033 (US)  
Inventor : Gallagher, John James  
18 Pembroke Drive  
Turnersville, New Jersey 08012 (US)

(74) Representative : Lupton, Frederick  
LONDON PATENT OPERATION, G.E.  
TECHNICAL SERVICES Co. INC., Essex  
House, 12/13 Essex Street  
London WC2R 3AA (GB)

(54) Radar system with active array antenna, elevation-responsive PRF control, and beam multiplex control.

(57) A multipurpose system provides radar surveillance for air traffic control purposes. The system includes four separate active phased-array antennas, each with  $\pm 45^\circ$  coverage in azimuth, from  $0^\circ$  to  $60^\circ$  in elevation. Each antenna element of each phased-array antenna is coupled by a low-loss path to the solid-state amplifier associated with a transmit-receive (TR) module. Each antenna produces a sequence of pencil beams, which requires less transmitted power from the TR modules than a fan beam, but requires more time because the pencil beam must be sequenced to cover the same volume as the fan beam. In order to scan the volume in a short time, the PRF is responsive to the elevation angle of the beam, so higher elevation angles use a higher PRF. Low elevation angle beams receive long transmitter pulses for high power, and pulse compression is used to restore range resolution, but the long pulse results in a large minimum range within which targets cannot be detected. A second scan is provided at low elevation angles with a short transmitter pulse to fill in the short-range coverage. Beams at higher elevation angles transmit pulse widths which are shorter than beams at low elevation angles, so that the minimum range requirement is met without a second scan, which also reduces the time required for volumetric scan. The number of pulses which are integrated to produce a return increases off-axis, to restore system margin lost due to off-axis power gain reduction. The volumetric scan rate is increased by a dynamic

scan regimen by which subsets of beams are pulsed with a high transmitter PRF but with a low effective beam PRF to reduce range ambiguity and preserve Doppler resolution without the usual increase of scan time. For best range resolution, Doppler processing is used, with range sidelobe pulse suppression applied separately to each Doppler frequency bin.




FIG. 2a

EP 0 509 843 A3



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number

EP 92 30 3498

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 5)
Y	EP-A-0 320 306 (NEC CORP.) * Abstract; page 2, lines 5-35; page 2, line 62 - page 5, line 27 *	1,5-7	G 01 S 13/42 G 01 S 13/22 G 01 S 13/58 G 01 S 13/87 H 01 Q 3/46
Y	US-A-4 951 059 (TAYLOR, Jr.) * Abstract; column 2, lines 28-68; column 4, line 19 - column 6, line 49 *	1,5-7	
A	US-A-4 901 032 (KOMIAK) * Abstract; column 1, lines 5-13 *	2-4	
A	US-A-3 833 904 (GEBHARDT et al.) * Abstract; column 1, line 33 - column 2, line 41; column 4, line 4 - column 5, line 44; column 7, line 51 - column 8, line 37; column 9, line 13 - column 12, line 62; column 16, lines 14-31; column 17, line 45 - column 18, line 38; columns 237-240, claims 1-15 *	1,5-7	
A	US-A-4 053 884 (CANTRELL et al.) * Abstract *	1,7	TECHNICAL FIELDS SEARCHED (Int. Cl. 5)
A	AVIATION WEEK & SPACE TECHNOLOGY, vol. 133, no. 1, 2nd July 1990, pages 49-51, New York, US; B.D. NORDWALL: "Sweden develops new radar, computer for Gripen and airborne early warning" * Whole article *	1,7	G 01 S H 01 Q
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>17-02-1993</b>	Examiner <b>OLDROYD</b>
<b>CATEGORY OF CITED DOCUMENTS</b> X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 180 (01.82) (P001)